

CareFusion LTV 950

Product Specifications

Dimensions

Height 3 inches (8 cm) 3.25 inches (8.4 cm)Width 10 inches (25 cm) 10.5 inches (27 cm)Depth 12 inches (30 cm) 13.5 inches (38 cm)

Weight

Bare 12.85 lbs (5.83 kg)Loaded 14.45 lbs (6.5 kg)

Power indicators

External power: Green(Full Power), Amber(Low Power)Charge status: Flashing Amber(Pretest), Green(Charge Complete), Amber(Charging), Red(Charger or Battery Fault)Battery level: Green(Acceptable), Amber(Low), Red(Critically Low)

Monitors and Indications

Peak inspiratory pressure: 0 to 120 cmH2OMean airway pressure: 0 to 99 cmH2OPEEP: 0 to 99 cmH2OTotal breath rate: 0 to 250 bpmAirway pressure display: -10 to 108 cmH2OInhale/Exhale ratio: 99:1 to 1:99Calculated peak flow: 10 to 100 lpmPatient effort: Green LED

Alarms

Disconnect/sense lineLow and lost external powerLow and empty internal batteryApnea interval 10 to 60 secondsHigh pressure limit 5 to 100 cmH2OLow peak pressure Off, 1 to 60 cmH2OAlarm volume 60 to 80 dBA at 1 meterAlarm silence/reset 60 secondsVentilator inoperative Red LED, audible alarm

Power Cord

Biomed replaceable 2.75 m (9 ft)

Extended Features



NPPV (Non-Invasive Positive Pressure Ventilation) modeApnea back-up ventilation

The LTV-Series of Ventilators all look, act, and, feel alike with the exception of which controls and features are installed in each model. The following list is unique to this model.

- Pressure control
- Volume control
- Pressure support
- Flow-Triggering
- Leak Compensation
- Multiple power source
- Non-invasive ventilation
- Low pressure 02 inlet

Get the User Manual Here