

Product Specifications

		nensions					
17	m	Δ	n	C	$\boldsymbol{\cap}$	'n	c
$\boldsymbol{-}$		C		3	ıv	41	13

8" H x 8" W x 6" D, excluding pole clamp

Weight

9.5 lbs. with battery

Casing

High-impact plastic

Delivery Rate Range

Lines A & B:

0.1-99.9 ml/hr in 0.1 ml increments100-999 ml/hr in 1 ml increments

Concurrent Delivery

0.5 ml/hr minimum for each line

Plum Set

500 ml/hr cumulative (A+B) maximum

KVO



1.0 ml/hr or the last primary delivery rate, whichever is less

VTBI Range

0.1-99.9 ml in 0.1 ml increments 100-9999 ml in 1 ml increments

Electrical Power Requirements

120V, 50-60 Hz, 35VA

Fuses

F1, F2, 250V, 0.5A

Power Cord

Hospital Grade AC Cord 10 ft long

Battery

One sealed lead acid, rechargeable 6V battery, internal

Battery Life

With a new fully charged battery, the infuser shall operate for a minimum of 6 hours at 125 ml/hr or less, or deliver 500 ml at 126 ml/hr or greater on one line.



Recharge

The battery charges whenever the pump is connected to AC power. The recharge time is approximately 6 hours with the device operating at 125 ml/hr on one line.