

## **Product Specifications**

## Dimensions

Approximately 8.25H x 7.5W x 8.75D inches (including pole clamp)

## Weight

Approximately 7.75 lbs (with battery)

## Casing

High-impact plastic

#### **Power Requirements**

100-130 Vac, 50 to 60 Hz, less than 35 W

#### **Power Cord**

Hospital-grade AC (mains) cord. 10 feet long, with transparent plug

#### Fuses

0.5 A, 250 V. slo-blo



#### Battery

Sealed lead-acid rechargeable 8 V battery, internal to infusion system. Accessible for ease of field replacement, with color-coded leads and polarized connector.

## **Battery Operation**

A fully charged new battery will provide eight hours of operation at 125 ml/hr, or 1000 ml total volume delivered, whichever occurs first

## Recharge

The battery charges whenever the infusion system is connected to AC (mains) power. If the infusion system is operating at 125 ml/hr, a full recharge takes approximately 16 hours. If the infusion system is turned to OFF/CHARGE, recharge takes approximately eight hours.

#### **Delivery Rate Range**

Micro Mode:

.1 to 99.9 ml/hr

Macro Mode:

1 to 999 ml/hr (in 1 ml increments)

## KVO

1 ml/hr



# Dose Limit Range

1 to 9999 ml/hr (in 1 ml increments)

# **Occlusion Range**

10 psig (+5, -2 psig)